

EATON FULLER TRANSMISSIONER, MIDDEL BELASTNING FS-6205A



GEAR Eaton-Fuller 6205 5/1
Kapacitet: 8,99 liter

ANVEND	KLIMA
Motorvejsanvendelse, startservice	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Skift alle 8000 km

ANVEND	KLIMA
Motorvejsanvendelse, startservice	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Skift alle 8000 km

ANVEND	KLIMA
Terrænanvendelse, svær	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Kontroller alle 40 timer, skift alle 500 timer

ANVEND	KLIMA
Terrænanvendelse, svær	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Kontroller alle 40 timer, skift alle 500 timer

ANVEND	KLIMA
Terrænanvendelse	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Kontroller alle 40 timer, skift alle 1000 timer

ANVEND	KLIMA
Terrænanvendelse	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Kontroller alle 40 timer, skift alle 1000 timer

ANVEND	KLIMA
Motorvejsanvendelse	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50

Kontroller alle 16000 km, skift alle 80000 km

EATON FULLER TRANSMISSIONER, MIDDEL BELASTNING FS-6205A



ANVEND		KLIMA
Motorvejsanvendelse		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Kontroller alle 16000 km, skift alle 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.