

EATON FULLER TRANSMISSIONER, MIDDEL BELASTNING FSO-6109



GEAR Eaton-Fuller 6109 9/1
Kapacitet: 8,5 liter

ANVEND

Terrænanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

Gearlube GL-4 80W-90

Skift alle 30 timer

ANVEND

Terrænanvendelse, startservice

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Skift alle 30 timer

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

Gearlube GL-4 80W-90

Skift alle 8000 km

ANVEND

Motorvejsanvendelse, startservice

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Skift alle 8000 km

ANVEND

Terrænanvendelse, svær

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

Gearlube GL-4 80W-90

Kontroller alle 40 timer, skift alle 500 timer

ANVEND

Terrænanvendelse, svær

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 40 timer, skift alle 500 timer

ANVEND

Terrænanvendelse

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

PRODUKTANBEFALING 3

Gearlube GL-4 80W-90

Kontroller alle 40 timer, skift alle 1000 timer

EATON FULLER TRANSMISSIONER, MIDDEL BELASTNING FSO-6109



ANVEND		KLIMA
Terrænanvendelse		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 30	SP Gear 5015	Gearlube GL-4 80W

Kontroller alle 40 timer, skift alle 1000 timer

ANVEND		KLIMA
Motorvejsanvendelse		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90

Kontroller alle 20000 km, skift alle 100000 km/ 12 måneder

ANVEND		KLIMA
Motorvejsanvendelse		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 30	SP Gear 5015	Gearlube GL-4 80W

Kontroller alle 20000 km, skift alle 100000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.