

ERF E6 E6.21P (1993-1996)



MOTOR Perkins Phaser 210
Kapacitet: 11,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SHPD 15W-40		

Skift alle 20000 km

DIFFERENTIALE BAG (4x2) Rockwell

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

GEAR MANUEL Eaton 6109 9/1
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube GL-4 80W	

Kontroller alle 16000 km, skift alle 100000 km

HYDRAULISK TIPPESYSTEM FOR KABINEN

Kapacitet: 0,43 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 16000 km

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

**SERVOSTYRING**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D*Skift alle 200000 km/ 12 måneder***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 16000 km***SMØREPUNKTER/NIPLER ANHÆNGERTRÆK**

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 16000 km***KØLESYSTEM**

Kapacitet: 32 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.