

ERF EC8 EC 8.30 (4X2/6X2) (1996-2002)



MOTOR Cummins C300
Kapacitet: 23,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 25000 km/ 6 måneder

DIFFERENTIALE BAG Rockwell S153
Kapacitet: 16,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

DIFFERENTIALE BAG Rockwell S160
Kapacitet: 16,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

GEAR AUTOMATISK Allison HD4560P 6/1
Kapacitet: 48 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

ATF Dexron II-D

GEAR MANUEL Eaton FS-8209A 9/1
Kapacitet: 8,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 16000 km, skift alle 100000 km/ 6 måneder

ERF EC8 EC 8.30 (4X2/6X2) (1996-2002)



GEAR MANUEL Eaton RTX 11609 A 9/1
Kapacitet: 13 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 16000 km, skift alle 100000 km/ 6 måneder

GEAR MANUEL ZF 9S-109 9/1
Kapacitet: 8,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube GL-4 80W	

Kontroller alle 16000 km, skift alle 100000 km/ 6 måneder

HYDRAULISK TIPPESYSTEM FOR KABINEN

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 16000 km

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 4,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 16000 km

ERF EC8 EC 8.30 (4X2/6X2) (1996-2002)



SMØREPUNKTER/NIPLER ANDRE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER ANHÆNGERTRÆK

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

Kontroller alle 16000 km

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.