

ERF ES6 ES 6.23 (4X2/6X2) (1996-2002)



MOTOR Cummins B235
Kapacitet: 16,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 25000 km/ 6 måneder

DIFFERENTIALE BAG Rockwell S153
Kapacitet: 16,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder

GEAR AUTOMATISK Allison MD 3560P 5/1
Kapacitet: 27 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

ATF Dexron II-D

GEAR MANUEL Eaton FS-6109A 9/1
Kapacitet: 8,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 16000 km, skift alle 100000 km/ 6 måneder

HYDRAULISK TIPPESTYSE FOR KABINEN

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 16000 km

**HYDRAULISK KOBLINGSSYSTEM**

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3*Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder***SERVOSTYRING**

Kapacitet: 4,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D*Kontroller alle 16000 km***SMØREPUNKTER/NIPLER ANDRE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**SMØREPUNKTER/NIPLER ANHÆNGERTRÆK**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Kontroller alle 16000 km***KØLESYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 16000 km, skift alle 200000 km/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.