

FODEN 3000 3000 S108R3 - 265 6CTAA-265 (1988-1996)



MOTOR 6CTAA-265
Kapacitet: 22,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

DIFFERENTIALE BAG BUGSERE Eaton DS 401-P
Kapacitet: 17 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2
Gearlube GL-5 85W-140

PRODUKTANBEFALING 3
Unigear LS GL-3/GL-5 85W-140

DIFFERENTIALE BAG FØRE Eaton DS 401-P
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2
Gearlube GL-5 85W-140

PRODUKTANBEFALING 3
Unigear LS GL-3/GL-5 85W-140

GEAR MANUEL Eaton 6109 9/1
Kapacitet: 8,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Gearlube GL-4 80W

HYDRAULISK TIPPESTYSTEM FOR KABINEN
Kapacitet: 1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

FODEN 3000 3000 S108R3 - 265 6CTAA-265 (1988-1996)



HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM 300TX, 325TX

Kapacitet: 45 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

KØLESYSTEM 6CTAA

Kapacitet: 38 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

FODEN 3000 3000 S108R3 - 265 6CTAA-265

(1988-1996)

**KØLESYSTEM** LTAA10-300; LTAA10-325

Kapacitet: 39 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

STYRETØJ		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.