

FORD OTOSAN CARGO CARGO 1824 4X2 (2004-2007)



MOTOR Ford EcoTorq
Kapacitet: 28 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

DIFFERENTIALE BAG Meritor RS186
Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 85W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

GEAR MANUEL ZF 9S-75 9/1
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

HYDRAULISK KOBLINGSSYSTEM
Kapacitet: 0,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

SERVOSTYRING
Kapacitet: 3,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

FORD OTOSAN CARGO CARGO 1824 4X2 (2004-2007)



SMØREPUNKTER/NIPLER HJULLEJER DRIVAKSEL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

SMØREPUNKTER/NIPLER HJULLEJER FOR

Kapacitet: 100 gram (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

SMØREPUNKTER/NIPLER STYREBOLTE

Kapacitet: 15 gram (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

KØLESYSTEM

Kapacitet: 17,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

KLIMAANLÆGSKOMPRESSOR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.