

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



MOTOR DAF MX
Kapacitet: 39 liter

ANVEND

On-Highway

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Armado Synth LSP 10W-40

Skift alle 45000 km/ 12 måneder/ 1000 timer

ANVEND

Vej, foretrukket

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Armado Synth LSP 10W-40

Skift alle 90000 km/ 12 måneder/ 2000 timer

ANVEND

Offroad & erhverv

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Armado Synth LSP 10W-40

Skift alle 30000 km/ 12 måneder/ 1000 timer

ANVEND

Offroad & erhverv, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Armado Synth LSP 10W-40

Skift alle 60000 km/ 12 måneder/ 2000 timer

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



DIFFERENTIALE BAG BUGSERE DAF 1355T
Kapacitet: 13 liter, Kapacitet: 2 liter (hvert nav)

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 3000 km/ 2 måneder/ 100 timer

ANVEND	KLIMA
On-Highway	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 2000 timer

ANVEND	KLIMA
Offroad & erhverv	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 3000 timer

DIFFERENTIALE BAG FØRE DAF 1355T
Kapacitet: 18 liter, Kapacitet: 2 liter (hvert nav)

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 3000 km/ 2 måneder/ 100 timer

ANVEND	KLIMA
On-Highway	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 2000 timer

ANVEND	KLIMA
Offroad & erhverv	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 3000 timer

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



GEAR AUTOMATISK ZF 16AS-2630 16/2
Kapacitet: 12 liter, Kapacitet: 13 liter (+ "Intarder")

ANVEND	KLIMA
On-Highway	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 120000 km/ 12 måneder/ 2600 timer

ANVEND	KLIMA
Vej, foretrukket	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 240000 km/ 24 måneder/ 5300 timer

ANVEND	KLIMA
Offroad & erhverv	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 30	Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 3000 timer

ANVEND	KLIMA
Offroad & erhverv, udvidet	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 180000 km/ 24 måneder/ 6000 timer

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



GEAR MANUEL ZF 16S-2220 16/2

Kapacitet: 10 liter, Kapacitet: 12 liter (+ "Intarder")

ANVEND

On-Highway

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Gearlube GL-4 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Skift alle 120000 km/ 12 måneder/ 2600 timer

ANVEND

Vej, foretrukket

KLIMA

Moderat

PRODUKTANBEFALING 1

Syngear MT/LD 75W-80

Skift alle 240000 km/ 24 måneder/ 5300 timer

ANVEND

Offroad & erhverv

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Gearlube GL-4 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 3000 timer

ANVEND

Offroad & erhverv, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Syngear MT/LD 75W-80

Skift alle 180000 km/ 24 måneder/ 6000 timer

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



GEAR MANUEL ZF 16S-2520 16/2

Kapacitet: 10 liter, Kapacitet: 12 liter (+ "Intarder")

ANVEND		KLIMA
On-Highway		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 30	Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 120000 km/ 12 måneder/ 2600 timer

ANVEND		KLIMA
Vej, foretrukket		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 240000 km/ 24 måneder/ 5300 timer

ANVEND		KLIMA
Offroad & erhverv		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 30	Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 90000 km/ 12 måneder/ 3000 timer

ANVEND		KLIMA
Offroad & erhverv, udvidet		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 180000 km/ 24 måneder/ 6000 timer

HYDRAULISK OPHÆNG BAGAKSEL HPVS / EVS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Skift alle 24 måneder

HYDRAULISK TIPPESYSTEM FOR KABINEN

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Skift alle 24 måneder

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Skift alle 24 måneder

BOGIE OMDREJNINGSAKSEL SMURT I OLIE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

CENTRALT SMØRINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 00/000		

HJULLEJER FORAKSLER DAF 182N/186N

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 6 måneder

GINAF X-SERIE EURO 4 + 5 X4241S EURO 4/5 8X4 (2006-2014)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 6 måneder

KØLESYSTEM

Kapacitet: 31-32,6 liter, Kapacitet: 41 liter (+ "Intarder")

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.