

IVECO M SERIER M-RANGE 175.17 (1988-1992)



MOTOR 8060.25

Kapacitet: 12,2 liter, Filterkapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

DIFFERENTIALE BAG (4x2) Rockwell S160E

Kapacitet: 16,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

GEAR MANUEL ZF S6-36 + GV 12/2

Kapacitet: 11,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Gearlube GL-4 80W-90

IVECO M SERIER M-RANGE 175.17 (1988-1992)



GEAR MANUEL ZF S6-36 6/1
Kapacitet: 9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Gearlube GL-4 80W-90

HYDRAULISK TIPPESTYSTEM FOR KABINEN
Kapacitet: 0,35 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
LHM +		

HYDRAULISK KOBLINGSSYSTEM
Kapacitet: 0,4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

SERVOSTYRING ZF 8043 / HDS 450 Riva e Calzoni
Kapacitet: 3,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

KØLESYSTEM
Kapacitet: 22 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.