

IVECO STRALIS CURSOR 13 (HI-WAY / ROAD / STREET) STRALIS 440S56 (6X2) EURO 5 (2013 OG EFTER)



MOTOR Cursor 13
Kapacitet: 28 liter

ANVEND	KLIMA
Foretrukket, svovlniveau i brændstof >0,5%	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	

Skift alle 75000 km/ 6 måneder

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	

Skift alle 150000 km/ 12 måneder

ANVEND	KLIMA
Acceptabelt svovlniveau i brændstof >0,5%	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Skift alle 50000 km/ 6 måneder

ANVEND	KLIMA
Acceptabel	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Skift alle 100000 km/ 12 måneder

DIFFERENTIALE BAG MS 13175
Kapacitet: 12,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 200000 km/ 24 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 200000 km/ 24 måneder

IVECO STRALIS CURSOR 13 (HI-WAY / ROAD / STREET) STRALIS 440S56 (6X2) EURO 5 (2013 OG EFTER)



DIFFERENTIALE BAG MED SKIVEBREMSE MS 13175

Kapacitet: 12,5 liter

ANVEND		KLIMA
Foretrukne		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Skift alle 450000 km/ 36 måneder

ANVEND		KLIMA
Acceptabel		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 200000 km/ 24 måneder

ANVEND		KLIMA
Acceptabel		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 200000 km/ 24 måneder

GEAR AUTOMATISK ZF 12AS-2530 TO (EuroTronic) 12/2

Kapacitet: 12 liter, Kapacitet: 21 liter (+ "Intarder")

ANVEND		KLIMA
Normal (alternativ)		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 300000 km/ 24 måneder

ANVEND		KLIMA
Krævende (alternativ)		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 240000 km/ 24 måneder

IVECO STRALIS CURSOR 13 (HI-WAY / ROAD / STREET) STRALIS 440S56 (6X2) EURO 5 (2013 OG EFTER)



GEAR MANUEL ZF 16S-2520 TO 16/2

Kapacitet: 13 liter, Kapacitet: 21,5 liter (+ "Intarder")

ANVEND

Normal (alternativ)

KLIMA

Moderat

PRODUKTANBEFALING 1

Syngear MT/LD 75W-80

Skift alle 300000 km/ 24 måneder

ANVEND

Krævende (alternativ)

KLIMA

Moderat

PRODUKTANBEFALING 1

Syngear MT/LD 75W-80

Skift alle 240000 km/ 24 måneder

HYDRAULISK TIPPESTYSTEM FOR KABINEN

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 150000 km/ 12 måneder, skift alle 36 måneder

SERVOSTYRING

Kapacitet: 2,7 liter, Kapacitet: 13,5 liter (med bagstyreaksel)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

IVECO STRALIS CURSOR 13 (HI-WAY / ROAD / STREET) STRALIS 440S56 (6X2) EURO 5 (2013 OG EFTER)



SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Multi Purpose Grease 3

KØLESYSTEM

Kapacitet: 44 liter, Kapacitet: 64 liter (+ "Intarder")

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Kontroller alle 12 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.