

MERITOR ENKELT REDUKTIONSAKSLE - MX, RF, RS RS-16-141



DIFFERENTIALE STYRET AKSEL

Kapacitet: 15,9 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 40000 km, skift alle 160000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Kontroller alle 40000 km, skift alle 160000 km/ 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 40000 km, skift alle 160000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.