

PACCAR MX SERIER MX-13 EPA 10 (2012-2015)



MOTOR Paccar MX-13
Kapacitet: 40 liter

ANVEND	KLIMA
Ekstremt hård belastning	Moderat

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Skift alle 25000 mil/ 12 måneder/ 800 timer

ANVEND	KLIMA
Linjetransport, tomgangstid > 20 %	Moderat

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Skift alle 40000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Linjetransport, tomgangstid < 20 % og motorens softwareniveau ESB E070 eller højere	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Skift alle 60000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Linjetransport, tomgangstid < 20 %	Moderat

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Skift alle 60000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Linjetransport, tomgangstid > 20 % og motorens software niveau ESB E070 eller højere	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Skift alle 40000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Ekstremt hård belastning, motorens softwareniveau ESB E070 eller højere	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Skift alle 25000 mil/ 12 måneder/ 800 timer

PACCAR MX SERIER MX-13 EPA 10 (2012-2015)



KØLESYSTEM

Kapacitet: 53-57 liter

ANVEND

Vejkørsel

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 750000 mil/ 72 måneder/ 22000 timer

ANVEND

Terrænkørsel

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 96 måneder/ 15000 timer

SCR (SELECTIVE CATALYTIC REDUCTION)-SYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.