

PACCAR MX SERIER MX 430 (2010-2012)



MOTOR Paccar MX
Kapacitet: 40 liter

ANVEND	KLIMA
Brændstofforbrug > 6 mpg og GVW < 80.000 lbs	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Skift alle 40000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Brændstofforbrug > 6 mpg og GVW < 80.000 lbs	Arktisk

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

Skift alle 40000 mil/ 12 måneder/ 1200 timer

ANVEND	KLIMA
Brændstofforbrug < 6 mpg eller GVW < 80.000 lbs	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Skift alle 25000 mil/ 12 måneder/ 800 timer

ANVEND	KLIMA
Brændstofforbrug < 6 mpg eller GVW < 80.000 lbs	Arktisk

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

Skift alle 25000 mil/ 12 måneder/ 800 timer

ANVEND	KLIMA
Erhvervsmæssig	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Skift alle 25000 mil/ 12 måneder/ 800 timer

ANVEND	KLIMA
Erhvervsmæssig	Arktisk

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

Skift alle 25000 mil/ 12 måneder/ 800 timer

PACCAR MX SERIER MX 430 (2010-2012)**KØLESYSTEM**

Kapacitet: 53-57 liter

ANVEND

Vejkørsel

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Skift alle 750000 mil/ 72 måneder/ 22000 timer*

ANVEND

Terrænkørsel

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Skift alle 96 måneder/ 15000 timer***SCR (SELECTIVE CATALYTIC REDUCTION)-SYSTEM**

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.