

PACCAR PX-SERIEN PX-9 EPA 10 (2013-2016)

**MOTOR** Paccar PX-9

Kapacitet: 26,5 liter (Højkapacitetsolesump), Kapacitet: 22,7 liter (standardoliesump), Kapacitet: 25,6 liter (Standardoliesump med cylinderblokafstiverplade), Filterkapacitet: 3,78 liter

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed > 40 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 20000 mil/ 12 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 30 - 40 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 15000 mil/ 6 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 25 - 30 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 12000 mil/ 6 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 20 - 25 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 10500 mil/ 6 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 15 - 20 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 8500 mil/ 6 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 10 - 15 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 6000 mil/ 6 måneder/ 500 timer

ANVEND	KLIMA
Køretøjets gennemsnitlige hastighed 5 - 10 mph	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Skift alle 4000 mil/ 6 måneder/ 500 timer

PACCAR PX-SERIEN PX-9 EPA 10 (2013-2016)



ANVEND		KLIMA
Køretøjets gennemsnitlige hastighed < 5 mph		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40
Skift alle 1500 mil/ 6 måneder/ 500 timer		

KØLESYSTEM		
Kapacitet: 15,6 liter (Motor kun)		
ANVEND		KLIMA
Vejkørsel		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Skift alle 750000 mil/ 72 måneder/ 22000 timer		

ANVEND		KLIMA
Terrænkørsel		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Skift alle 96 måneder/ 15000 timer		

SCR (SELECTIVE CATALYTIC REDUCTION)-SYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.