

PETERBILT ERHVERVSLASTBILER 320

CUMMINS ISX15 (2009-2013)



MOTOR Cummins ISX
Kapacitet: 52,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

PRODUKTANBEFALING 2

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Armado Synth MSP 5W-40

Skift alle 15000 mil/ 6 måneder/ 400 timer

GEAR AUTOMATISK Allison

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 15000 mil, skift alle 25000 mil

GEAR MANUEL Fuller

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 50

Kontroller alle 15000 mil, skift alle 50000 mil

HYDRAULISK MOTORHJELMHOLDESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SERVOSTYRING Sheppard

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 15000 mil, skift alle 240000 mil/ 24 måneder

SERVOSTYRING TRW

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 15000 mil, skift alle 240000 mil/ 24 måneder

PETERBILT ERHVERVSLASTBILER 320

CUMMINS ISX15 (2009-2013)



HJULLEJER DRIVNAV OLIESMURT Eaton/Dana
Kapacitet: 0,92 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HJULLEJER IKKE-DRIVNAV OLIESMURT IKKE-LMS + OUTRUNNER-SEGL Eaton/Dana
Kapacitet: 0,3-0,4 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HJULLEJER IKKE-DRIVNAV OLIESMURT IKKE-LMS + STANDARDSEGL Eaton/Dana
Kapacitet: 0,3-0,4 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HJULLEJER IKKE-DRIVNAV OLIESMURT LMS Eaton/Dana
Kapacitet: 0,27 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO

Kontroller alle 15000 mil/ 6 måneder, skift alle 250000 mil/ 24 måneder/ 6000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.