

RENAULT (EU) MAGNUM DXI MAGNUM 440 DXI EURO 5 (2009-2014)



MOTOR DXi 13
Kapacitet: 33 liter

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Skift alle 100000 km/ 12 måneder

ANVEND	KLIMA
Fleksibel (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	Dieselfleet MSP 10W-30

Skift alle 80000 km/ 12 måneder

DIFFERENTIALE BAG P 13170 (RSS1344C)
Kapacitet: 17 liter

ANVEND	KLIMA
Stærk (foretrukket)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 1011	Syngear TDL 75W-90

Skift alle 240000 km/ 24 måneder

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 240000 km/ 24 måneder

ANVEND	KLIMA
Normal (foretrukne)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 1011	Syngear TDL 75W-90

Skift alle 400000 km/ 36 måneder

ANVEND	KLIMA
Krævende (alternativ)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 120000 km/ 24 måneder

RENAULT (EU) MAGNUM DXI MAGNUM 440

DXI EURO 5 (2009-2014)



GEAR HALVAUTOMATISK Optidriver+ AT 2412D (Volvo I-Shift) 12/3
Kapacitet: 14,5 liter

ANVEND		KLIMA
Normal (alternativ)		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 40		

Skift alle 120000 km/ 24 måneder

ANVEND		KLIMA
Normal (foretrukne)		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 400000 km/ 36 måneder

GEAR MANUEL ZF 16S-2230 TD 16/2
Kapacitet: 12,4 liter, Kapacitet: 21,5 liter (+ "Intarder")

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SERVOSTYRING
Kapacitet: 4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

KØLESYSTEM
Kapacitet: 44 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 16		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.