

RENAULT (EU) PREMIUM EURO 4/5

PREMIUM 410 DXI EURO 4/5 (4X2/6X2) (2006-2009)



MOTOR DXi 11
Kapacitet: 36,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	Dieselfleet MSP 10W-30

Skift alle 80000 km/ 24 måneder

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1		
Dieselfleet CD+ 15W-40		

Skift alle 40000 km/ 48 måneder

ANVEND	KLIMA
Fleksibel (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet MSP 10W-30	Dieselfleet CD+ 15W-40	

Skift alle 100000 km/ 24 måneder

ANVEND	KLIMA
Alvorlig, =>44 t	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	Dieselfleet MSP 10W-30

Skift alle 40000 km/ 48 måneder

ANVEND	KLIMA
Alvorlig (alternativ), =>44 t	Moderat

PRODUKTANBEFALING 1		
Dieselfleet CD+ 15W-40		

Skift alle 30000 km/ 24 måneder



RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 410 DXI EURO 4/5 (4X2/6X2) (2006-2009)



DIFFERENTIALE BAG P 13170 (RSS1344C)

Kapacitet: 17 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Skift alle 120000 km/ 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Skift alle 80000 km/ 24 måneder

DIFFERENTIALE BAG P 1395

Kapacitet: 17,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Skift alle 120000 km/ 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Skift alle 80000 km/ 12 måneder

GEAR HALVAUTOMATISK AT 2412C (Optidriver+) 12/4

Kapacitet: 14,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 400000 km/ 36 måneder

RENAULT (EU) PREMIUM EURO 4/5

PREMIUM 410 DXI EURO 4/5 (4X2/6X2) (2006-2009)



GEAR MANUEL ZF 16S-1820 TO 16/2
Kapacitet: 8 liter, Kapacitet: 11 liter (+ "Intarder")

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 300000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 200000 km/ 24 måneder

GEAR MANUEL ZF 16S-1920 TD 16/2
Kapacitet: 10 liter, Kapacitet: 21,5 liter (+ "Intarder")

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 300000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 200000 km/ 24 måneder

NAVREDUKTIONER BAG P 1395
Kapacitet: 0,4 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Skift alle 120000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Skift alle 80000 km/ 12 måneder

RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 410 DXI EURO 4/5 (4X2/6X2) (2006-2009)



RETARDER Voith R 115
Kapacitet: 6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Syngear MT/LD 75W-80

Skift alle 180000 km/ 24 måneder

SERVOSTYRING
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Almirol

KØLESYSTEM
Kapacitet: 44 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.