

# SEDDON ATKINSON EUROMOVER

## EUROMOVER L619275FSD (4X2) (2001-2007)



**MOTOR** Iveco F2BE0681C Cursor 8  
Kapacitet: 23 liter, Filterkapacitet: 2,5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                           |                               |                               |
|---------------------------|-------------------------------|-------------------------------|
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Armado Synth 5W-30</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Skift alle 80000 km/ 1600 timer/ 12 måneder*

**DIFFERENTIALE BAG** Meritor U 177 E  
Kapacitet: 18,5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                 |                              |                                     |
|---------------------------------|------------------------------|-------------------------------------|
| PRODUKTANBEFALING 1             | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3                 |
| <b>Gearlube HS GL-5 80W-140</b> | <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

*Kontroller alle 80000 km/ 12 måneder/ 1600 timer, skift alle 160000 km/ 3200 timer*

**GEAR AUTOMATISK** Allison MD 3560P 5/1  
Kapacitet: 18 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                     |  |
|----------------------|---------------------|--|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

*Kontroller alle 80000 km/ 12 måneder/ 1600 timer, skift alle 120000 km/ 3000 timer/ 36 måneder*

### HYDRAULISK TIPPESTYSTEM FOR KABINEN

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 15</b>  |  |  |

*Kontroller alle 80000 km/ 12 måneder/ 1600 timer*

### SERVOSTYRING

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                     |  |
|----------------------|---------------------|--|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

*Kontroller alle 80000 km/ 12 måneder/ 1600 timer*

# SEDDON ATKINSON EUROMOVER

## EUROMOVER L619275FSD (4X2) (2001-2007)



**HJULLEJER OLIESMURT** Meritor U 177 E  
Kapacitet: 0,35 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube HS GL-5 80W-140**

PRODUKTANBEFALING 2  
**Gearlube GL-5 85W-140**

PRODUKTANBEFALING 3  
**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 80000 km/ 12 måneder/ 1600 timer, skift alle 160000 km/ 3200 timer

### SMØREPUNKTER/NIPLER

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

Kontroller alle 80000 km/ 12 måneder/ 1600 timer

### KØLESYSTEM

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Coolant -38 Organic NF**

PRODUKTANBEFALING 2  
**Coolant -26**

Kontroller alle 80000 km/ 12 måneder/ 1600 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.