

SEDDON ATKINSON STRATO STRATO R5 21.275NTA (6X2) (2001-2007)



MOTOR Iveco F4AE0681A*C Tector
Kapacitet: 10,8 liter, Filterkapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 80000 km/ 12 måneder

DIFFERENTIALE BAG Meritor U 177 E
Kapacitet: 18,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 80000 km/ 12 måneder, skift alle 160000 km/ 3200 timer

GEAR MANUEL Eaton 8309 A 9/1
Kapacitet: 7,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 80000 km/ 12 måneder

HYDRAULISK TIPPESYSTEM FOR KABINEN

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 15		

Kontroller alle 80000 km/ 12 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 80000 km/ 12 måneder

SEDDON ATKINSON STRATO STRATO R5 21.275NTA (6X2) (2001-2007)



SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 80000 km/ 12 måneder

HJULLEJER OLIESMURT Meritor U 177 E Kapacitet: 0,35 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 80000 km/ 12 måneder, skift alle 160000 km/ 3200 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 80000 km/ 12 måneder

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 80000 km/ 12 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.