

UD TRUCKS QUESTER QUESTER CKE 390 4X2R (2014 OG EFTER)



MOTOR UD GH11E
Kapacitet: 37,5 liter

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

PRODUKTANBEFALING 2

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Armado Synth MSP 5W-40

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

PRODUKTANBEFALING 2

Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Armado Synth LSP 10W-40

DIFFERENTIALE BAG RSS1348
Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

GEAR MANUEL 12-HASTIGHEDS STO2012 (F2R20A) 12/1

Kapacitet: 15 liter, Kapacitet: 16 liter (+ kraftudtag), Kapacitet: 15,8 liter (+ oliekløler), Kapacitet: 16,8 liter (+ oliekløler og PTO)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

GEAR MANUEL 9-HASTIGHEDS STO2009 (F9R20A) 9/1

Kapacitet: 14 liter, Kapacitet: 15 liter (+ kraftudtag), Kapacitet: 14,8 liter (+ oliekløler), Kapacitet: 15,8 liter (+ oliekløler og PTO)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

UD TRUCKS QUESTER QUESTER CKE 390 4X2R (2014 OG EFTER)



HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

SERVOSTYRING FAA10 (4x2, 6x2, 6x4) Kapacitet: 4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
HT Q9 High Grade Grease	Labora Grease	

KØLESYSTEM

Kapacitet: 49,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.