

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 OG EFTER)



MOTOR DAF WS 242 L
Kapacitet: 29 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Skift alle 20000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 20000 km

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Multifleet SCD 20W-20

Skift alle 20000 km

DIFFERENTIALE BAG ZF A-131
Kapacitet: 22 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 20000 km, skift alle 60000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 20000 km, skift alle 60000 km

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 OG EFTER)



GEAR MANUEL ZF S6-85 6/1
Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 40000 km, skift alle 60000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SCD 30

PRODUKTANBEFALING 2
SP Gear 5015

PRODUKTANBEFALING 3
Gearlube GL-4 80W

Kontroller alle 40000 km, skift alle 60000 km

GEAR MANUEL ZF S8-180 8/1
Kapacitet: 17 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 40000 km, skift alle 60000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SCD 30

PRODUKTANBEFALING 2
SP Gear 5015

PRODUKTANBEFALING 3
Gearlube GL-4 80W

Kontroller alle 40000 km, skift alle 60000 km

NAVREDUKTIONER BAG ZF A-131
Kapacitet: 0,7 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2
Gearlube GL-5 85W-140

PRODUKTANBEFALING 3
Unigear LS GL-3/GL-5 85W-140

Kontroller alle 20000 km, skift alle 60000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 20000 km, skift alle 60000 km

VDL (BOVA/BERKHOF) FH FUTURA FHD 10.340, FHD 12.340 (1991 OG EFTER)



HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 60000 km

SERVOSTYRING ZF 8043

Kapacitet: 10 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Skift alle 60000 km

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3

Kontroller alle 20000 km

KØLESYSTEM

Kapacitet: 50 liter, Kapacitet: 79 liter (+ varmeapparat)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.