

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



ENGINE D7E (Euro 4/5)
Capacity: 21-25 liter

USE	CLIMATE
Long distance, 45-68t, hilly, max 90 km/h, Europe, fuel =<50 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 50000 km/ 12 months/ 1200 hours

USE	CLIMATE
Long distance, =<26t, flat/hilly, max 90 km/h, Europe, fuel =<27 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 100000 km/ 12 months

USE	CLIMATE
Long distance, =<26t, hilly, max 90 km/h, Europe, fuel =<32 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 75000 km/ 12 months

USE	CLIMATE
Long distance, 27-44t, flat/hilly, max 90 km/h, Europe, fuel =<32 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 75000 km/ 12 months

USE	CLIMATE
Regional, =<18t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 100000 km/ 12 months

USE	CLIMATE
Regional, 19-26t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 75000 km/ 12 months

USE	CLIMATE
Regional, 27-44t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 50000 km/ 12 months/ 1200 hours

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Distribution, city, =<18t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 75000 km/ 12 months

USE		CLIMATE
Distribution, city, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 50000 km/ 12 months/ 1200 hours

USE		CLIMATE
Construction Site, =<18t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 50000 km/ 12 months/ 1200 hours

USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 30000 km/ 12 months/ 1200 hours

USE		CLIMATE
Construction Site, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 15000 km/ 12 months/ 600 hours

DIFFERENTIAL REAR RSH1140C Capacity: 17,3 liter, Capacity: 0,5 liter (each hub)		
USE		CLIMATE
All other conditions		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 120000 km/ 24 months

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Change every 120000 km/ 24 months

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Construction Site, extended, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, extended, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =>26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		

DIFFERENTIAL REAR RSS1125A
Capacity: 12,5 liter

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
All other conditions		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, extended, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, extended, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =>26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Construction Site, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Change every 80000 km/ 12 months

USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 400000 km/ 36 months

DIFFERENTIAL REAR RSS1332A Capacity: 17 liter

USE		CLIMATE
All other conditions		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 120000 km/ 24 months

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Change every 120000 km/ 24 months

USE		CLIMATE
Construction Site, extended, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 240000 km/ 24 months

USE		CLIMATE
Construction Site, 19-26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 80000 km/ 12 months

USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Change every 80000 km/ 12 months

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Construction Site, extended, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =>26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		
DIFFERENTIAL REAR HYPOID RSS1344B		
Capacity: 18,5 liter		
USE		CLIMATE
All other conditions		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 120000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, extended, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Construction Site, 19-26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, extended, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =>26t		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
Construction Site, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140
<i>Change every 80000 km/ 12 months</i>		
USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)

**POWER TAKE OFF**

Capacity: 4,5-5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 120000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Syngear MT/LD 75W-80	Gearlube GL-4 80W

Change every 120000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 10000 km/ 1 months

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Syngear MT/LD 75W-80	Gearlube GL-4 80W

Change every 10000 km/ 1 months

TRANSMISSION AUTOMATED I-Shift ATO1056 6/1

Capacity: 9,3 liter

USE		CLIMATE
Distribution, city, 19-26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

USE		CLIMATE
Construction Site, =<18t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 300000 km/ 24 months

USE		CLIMATE
Construction Site, very hilly, =>26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

TRANSMISSION AUTOMATIC Allison AL 306 6/1 Capacity: 18 liter, Capacity: 22 liter (+ retarder)

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 40000 km/ 12 months/ 1000 hours

USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 20000 km/ 6 months/ 500 hours

USE		CLIMATE
Construction Site, very hilly, =>26t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 20000 km/ 6 months/ 500 hours

TRANSMISSION MANUAL ZF ZTO1006 6/1 Capacity: 9 liter

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE		CLIMATE
Distribution, city, 19-26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =<18t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, 19-26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
All other conditions, extended		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 300000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, very hilly, =>26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		
TRANSMISSION MANUAL ZF ZTO1109 9/1		
Capacity: 8,5 liter		
USE		CLIMATE
Distribution, city, 19-26t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		
USE		CLIMATE
Construction Site, =<18t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



USE	CLIMATE
Construction Site, 19-26t	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 240000 km/ 24 months*

USE	CLIMATE
All other conditions, extended	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 300000 km/ 24 months*

USE	CLIMATE
Construction Site, very hilly, =>26t	Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80*Change every 240000 km/ 24 months***BOGIE LIFT**

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

PRODUCT RECOMMENDATION 2

Perlus H 15*Change every 12 months***HYDRAULIC ACTUATOR ATO1056**

Capacity: 1 liter

USE	CLIMATE
At overhauls only	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013**HYDRAULIC CAB TILT SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 15

VOLVO (EU) FL EURO 4/5 FL 240 EURO 5 (INCENTIVE) D7E (2006-2009)



HYDRAULIC SYSTEM REAR AXLE STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

POWER STEERING

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

COOLING SYSTEM

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.