

BMC MEGASTAR MEGASTAR 290 (2005-2011)



ENGINE BMC 2.8 CRI (VM R428 DOHC)
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Change every 10000 km/ 6 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Change every 5000 km

DIFFERENTIAL REAR BMC 135T
Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10000 km/ 6 months, change every 60000 km/ 12 months

TRANSMISSION MANUAL BMC 15 5/1
Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Check every 10000 km/ 6 months, change every 60000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

BMC MEGASTAR MEGASTAR 290 (2005-2011)**POWER STEERING**

Capacity: 2,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D****GREASE POINTS/NIPPLES GENERAL****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2****COOLING SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.