

CHEVROLET (USA / CAN) SILVERADO

GMT901 SILVERADO 4.3 V6 (2006-2010)



ENGINE LU3 Vortec
Capacity: 4,3 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Xedoz FE 5W-30

Change every 12 months

DIFFERENTIAL REAR
Capacity: 2,03-2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSMISSION AUTOMATIC 4/1
Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 12 months, change every 100000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 12 months, change every 50000 miles

CHEVROLET (USA / CAN) SILVERADO

GMT901 SILVERADO 4.3 V6 (2006-2010)


TRANSMISSION AUTOMATIC 6L80-E 6/1

Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 12 months, change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 12 months, change every 50000 miles*
TRANSMISSION AUTOMATIC 6L90-E 6/1

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 12 months, change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 12 months, change every 50000 miles*
TRANSMISSION AUTOMATIC Allison MW7 6/1

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 150000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 50000 miles*

CHEVROLET (USA / CAN) SILVERADO

GMT901 SILVERADO 4.3 V6 (2006-2010)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

COOLING SYSTEM

Capacity: 15,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 12 months, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.