

CHRYSLER (EU) GRAND VOYAGER GRAND VOYAGER 2.5 CRD (2001-2005)

**ENGINE**

Capacity: 6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	Asyntho 5W-30	

Change every 20000 km/ 12 months

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 10000 km/ 6 months

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	Asyntho 5W-30	

*Change every 10000 km/ 6 months***TRANSAXLE MANUAL NV T850 5/1**

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Check every 20000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 12 months, change every 24 months

CHRYSLER (EU) GRAND VOYAGER GRAND VOYAGER 2.5 CRD (2001-2005)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 13,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.