

# CHRYSLER (EU) VOYAGER VOYAGER 3.3I AWD (1990-1996)

**ENGINE**

Capacity: 4,3 liter, Filter capacity: 0,5 liter

| USE                      |                          | CLIMATE                     |
|--------------------------|--------------------------|-----------------------------|
| Normal                   |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    | <b>Synfleet SHPD 10W-40</b> |

*Check every 1000 km, change every 12000 km/ 12 months*

| USE                      |                          | CLIMATE                     |
|--------------------------|--------------------------|-----------------------------|
| Severe                   |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    | <b>Synfleet SHPD 10W-40</b> |

*Change every 4800 km/ 3 months***DIFFERENTIAL REAR (4x4)**

Capacity: 1,9 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 24000 km/ 24 months, change every 48000 km/ 48 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 3,8 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

*Check every 12000 km/ 12 months, change every 48000 km/ 48 months*

# CHRYSLER (EU) VOYAGER VOYAGER 3.3i

## AWD (1990-1996)



### TRANSFERBOX (4X4)

Capacity: 1,2 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 24000 km/ 24 months, change every 48000 km/ 48 months

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Severe                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Change every 29000 km

### HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Change every 24 months

### OVERRUNNING CLUTCH

Capacity: 0,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Severe                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

Change every 36000 km

### POWER STEERING

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

# CHRYSLER (EU) VOYAGER VOYAGER 3.3I AWD (1990-1996)



## GREASE POINTS/NIPPLES BALL JOINTS

| USE                            |                          | CLIMATE  |
|--------------------------------|--------------------------|----------|
| Normal                         |                          | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 |          |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     |          |

*Change every 12000 km/ 12 months*

## COOLING SYSTEM

Capacity: 8 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*