## CHRYSLER (EU) VOYAGER VOYAGER 3.3I (1990-1996)



ENGINE Capacity: 4,3 liter, Filter capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Asyntho 5W-30	Emperol 10W-40	Synfleet SHPD 10W-40	
Check every 1000 km, change every 12	000 km/ 12 months		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Asyntho 5W-30	Emperol 10W-40	Synfleet SHPD 10W-40	

Change every 4800 km/ 3 months

TRANSAXLE AUTOMATIC 3/1 Capacity: 3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 12000 km/ 12 months, change	every 48000 km/ 48 months	

HYDRAULIC BRAKE SYSTEM USE CLIMATE Normal Moderate

## PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4 Drauliquid DOT 3

Change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

## CHRYSLER (EU) VOYAGER VOYAGER 3.3I (1990-1996)



GREASE POINTS/NIPPLES BALL JOINTS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

Change every 12000 km/ 12 months

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
	•		

Change every 12000 km/ 12 months

COOLING SYSTEM Capacity: 8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.