Change every 7500 km/ 12 months

CITROËN C15 C 15E 1.0 (TU-ENGINE) (1988-1993)



ENGINE C1A/TU9 Capacity: 3,5 liter, Filter capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30		
Check every 3000 km, change every 10000 km/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30		

TRANSAXLE MANUAL 4/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 10000 km, change eve	ery 40000 km	'

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
		I

Check every 1000 km, change every 60000 km/24 months

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 1000 km, change every	/ 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.