CITROËN C15 C 15E 1.1 (E-ENGINE) (1987-1988)



Asyntho 5W-30

ENGINE E1A Capacity: 3,5 liter, Filter capacity: 0,5 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30			
Check every 3000 km, change every 10000 km/ 12 months					
USE		CLIMATE			
Severe		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			

Emperol 5W-40

Change every 7500 km/ 12 months

Specialsynth MSP 5W-40

TRANSAXLE MANUAL 4/1 Capacity: 2 liter			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		

Check every 10000 km, change every 40000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
01 1 10001 1	200001 /04 //	<u>'</u>	

Check every 1000 km, change every 60000 km/24 months

COOLING SYSTEM Capacity: 6,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 1000 km, change every	/ 24 months	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.