## CITROËN JUMPER / RELAY JUMPER / RELAY 2.8 HDI 4X4 (2002-2007)



<b>ENGINE</b> F.28 TDCR Capacity: 5,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 30000 km/36 months

<b>DIFFERENTIAL REAR</b> (4x4) Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSAXLE AUTOMATIC 4HP20 4/1		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 60000 km		

TRANSAXLE MANUAL ML5T 5/1 Capacity: 1,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km	·	

TRANSAXLE MANUAL MLGU5 5/7 Capacity: 2,7 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km	'	

## CITROËN JUMPER / RELAY JUMPER / RELAY 2.8 HDI 4X4 (2002-2007)



TRANSAXLE MANUAL MLUC 5/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,1 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				
Check every 60000 km				

TRANSFERBOX (4x4) Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 30000 km, change every	24 months	'

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 30000 km

use Normal		climate Moderate
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

PRODUCT RECOMMENDATION

## CITROËN JUMPER / RELAY JUMPER / **RELAY 2.8 HDI 4X4** (2002-2007)



COOLING SYSTEM Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 30000 km, change eve	rv 120000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.