CITROËN NEMO A9 NEMO 1.4I (2009-2011)



ENGINE TU3 Capacity: 3 liter (Service fill), Filter capacity: 0,25 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30		
Change every 30000 km/24 months	5			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30		
Change every 20000 km/ 12 months				

TRANSAXLE MANUAL MA5 5/1 Capacity: 2,1 liter (Dry fill), Capacity: 2 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	Gearlube RPC 75W-80			
Check every 24 months/ 30000 km	·			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	Gearlube RPC 75W-80			

SP Gear 5015	Gearlube RPC 75W-80	
Check every 20000 km/ 12 months		·
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	ax.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 30000 km, change every	24 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 20000 km, change every	24 months	

CITROËN NEMO A9 NEMO 1.4I (2009-2011)



POWER STEERING Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Check every 12 months/ 30000 km	

COOLING SYSTEM Capacity: 5,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 24 months/ 30000 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

AIRCONDITIONING COMPRESSOR Capacity: 135 CM3

Check every 20000 km/12 months

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.