CITROËN NEMO A9 NEMO 1.4I (2012-2015)



ENGINE TU3 Capacity: 3 liter (Service fill), Filter	capacity: 0,25 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Change every 30000 km/ 24 month	IS	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Change every 20000 km/ 12 months

TRANSAXLE MANUAL MA5 5/1 Capacity: 2,1 liter (Dry fill), Capacity: 2 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Gear 1081				
Check every 24 months/ 30000 km				
USE	CLIMATE			
Severe	Moderate			

PRODUCT RECOMMENDATION 1

SP Gear 1081

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km, change every 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Check every 20000 km, change every 24 months		

CITROËN NEMO A9 NEMO 1.4I (2012-2015)



POWER STEERING Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Charle avery 12 menths/ 20000 km		

Check every 12 months/ 30000 km

COOLING SYSTEM Capacity: 5,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 24 months/ 30000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months

AIRCONDITIONING COMPRESSOR Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.