

# DAIHATSU HI JET HIJET VAN / PICK UP 1.3

(1996-2005)

**ENGINE HC-ES**

Capacity: 3,5 liter, Filter capacity: 0,2 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**HDX 30***Change every 15000 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

PRODUCT RECOMMENDATION 2

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 3

**HDX 20W-50***Change every 15000 km/ 6 months*

| USE    | CLIMATE       |
|--------|---------------|
| Severe | Mediterranean |

PRODUCT RECOMMENDATION 1

**HDX 30***Change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

PRODUCT RECOMMENDATION 2

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 3

**HDX 20W-50***Change every 7500 km/ 6 months***DIFFERENTIAL REAR (4x2)**

Capacity: 1,15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSMISSION MANUAL 5/1**

Capacity: 1,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W-90***Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

# DAIHATSU HI JET HIJET VAN / PICK UP 1.3 (1996-2005)



## HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

## COOLING SYSTEM

Capacity: 5,7 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*