FIAT (EU) DUCATO 280, 290 DUCATO 2.0 (58 KW) 280 (1981-1990)



ENGINE 170B/XN1T Capacity: 4,6 liter, Capacity: 4,9 liter (Dry f	ill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Check every 500 km, change every 10000	km/ 6 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Synfleet SHPD 10W-40
Check every 500 km, change every 10000	km/ 6 months	

TRANSAXLE MANUAL 5/1 Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		

Check every 10000 km, change every 30000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 500 km, change every 24	nths

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 500 km, change every	60000 km/ 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.