

FIAT (EU) SCUDO 270 SCUDO 2.0 MULTIJET 130 (2011-2017)



ENGINE RH02
Capacity: 5,25 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Check every 3000 km, change every 30000 km/ 24 months

TRANSAXLE MANUAL 6/1
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 30000 km, change every 60000 km/ 24 months

ELECTRO-HYDRAULIC POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 24 months/ 30000 km

GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

FIAT (EU) SCUDO 270 SCUDO 2.0 MULTIJET 130 (2011-2017)

**COOLING SYSTEM**

Capacity: 9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 14+***Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.