

FORD (EU) P100 P 100 PICK-UP 1.8 TURBO DIESEL (1988-1992)

**ENGINE RFA**

Capacity: 5,5 liter, Filter capacity: 0,4 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 10000 km/ 6 months*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40*Change every 10000 km/ 6 months*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 10000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 20000 km/ 12 months***TRANSMISSION MANUAL N 5/1**

Capacity: 1,25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Syngear 75W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W-90*Check every 20000 km/ 12 months*

FORD (EU) P100 P 100 PICK-UP 1.8 TURBO DIESEL (1988-1992)



HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 60000 km/ 36 months

COOLING SYSTEM

Capacity: 9,5 liter

| USE | | CLIMATE |
|--------------------------|-------------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 11 | Coolant -38 Organic NF | Coolant -26 |

Change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.