

FORD (EU) TRANSIT V184/V185 TRANSIT

2.3 DOHC-16V (2000-2006)

**ENGINE DOHC 16V SEFI**

Capacity: 4,25 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Change every 20000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Check every 20000 km/ 12 months***TRANSMISSION MANUAL MT75 5/1**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 20000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 20000 km/ 12 months, change every 36 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 20000 km/ 12 months, change every 36 months*

FORD (EU) TRANSIT V184/V185 TRANSIT

2.3 DOHC-16V (2000-2006)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 7,8 liter, Capacity: 10,1 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.