PRODUCT RECOMMENDATION

FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (100) RWD EURO 5 (2012-2014)

ENGINE DRFA/DRFB/DRFC

Capacity: 10,5 liter (Initial fill), Capacity: 10,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		

Change every 50000 km/ 24 months

DIFFERENTIAL REAR

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 50000 km/ 24 months

TRANSMISSION MANUAL MT82 6/1

Capacity: 2,4 liter (Overhaul capacity), Capacity: 2,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 50000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 50000 km/ 12 months, change every 24 months

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 50000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (100) RWD EURO 5 (2012-2014)

POWER STEERING GREEN FLUID

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 50000 km/ 24 months

COOLING SYSTEM
Capacity: 10-13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 50000 km/ 24 months, change every 120 months

AIRCONDITIONING COMPRESSOR
Capacity: 280 CM3, Capacity: 640 CM3 (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM
Capacity: 730-770 grams, Capacity: 1366-1434 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367