FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (110) (2006-2011)



ENGINE QVFA Capacity: 6,14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza LSP 5W-30	Asyntho 5W-30	

Change every 25000 km/ 12 months

TRANSAXLE MANUAL VXT-75 5/ Capacity: 2,15 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Check every 25000 km/ 12 months		

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 25000 km/ 12 months, change every 24 months

HYDRAULIC CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 25000 km/ 12 months, change every 24 months

POWER STEERING GREEN FLUID FROM 10/2009 ONWARDS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 50000 km/24 months		

FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (110) (2006-2011)



POWER STEERING RED FLUID UPTO 10/2009		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Check every 50000 km/ 24 months	·	·

COOLING SYSTEM Capacity: 10-13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 25000 km/ 12 months	, change every 120 months	-

AIRCONDITIONING COMPRESSOR

Capacity: 280 CM3, Capacity: 640 CM3 (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 730-770 grams, Capacity: 1366-1434 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.