

# FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (140) (2007-2011)



**ENGINE PGFA**  
Capacity: 6,14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>

*Change every 25000 km/ 12 months*

**TRANSAXLE MANUAL VMT6 6/1**  
Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Gear 1081</b>	

*Check every 25000 km/ 12 months*

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Check every 25000 km/ 12 months, change every 24 months*

## HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Check every 25000 km/ 12 months, change every 24 months*

## POWER STEERING GREEN FLUID FROM 10/2009 ONWARDS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Fluid 3013</b>	

*Check every 50000 km/ 24 months*

# FORD (EU) TRANSIT V347/V348 TRANSIT 2.2 TDCI (140) (2007-2011)



## POWER STEERING RED FLUID UPTO 10/2009

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 4036</b>	<b>SP Matic 2032</b>	

Check every 50000 km/ 24 months

## COOLING SYSTEM

Capacity: 10-13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 25000 km/ 12 months, change every 120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 280 CM3, Capacity: 640 CM3 (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 730-770 grams, Capacity: 1366-1434 grams (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*