## FORD (USA) E-150 E-150 6.0 TURBO DIESEL (2008-2010)



<b>ENGINE</b> Power Stroke Capacity: 14,2 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Check every 1 months, change every 7500	) miles	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Check every 1 months, change every 7500	) miles	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Armado Synth MSP 5W-40		
Check every 1 months, change every 7500	) miles	
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Check every 1 months, change every 5000	) miles/ 6 months/ 200 hours	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Check every 1 months, change every 5000	) miles/ 6 months/ 200 hours	
USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Armado Synth MSP 5W-40		
Check every 1 months, change every 5000	) miles/ 6 months/ 200 hours	
USE		CLIMATE
Biodiesel B5		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Change every 5000 miles/ 200 hours		

## FORD (USA) E-150 E-150 6.0 TURBO DIESEL (2008-2010)



USE	CLIMATE
Biodiesel B5	Moderate
PRODUCT RECOMMENDATION 1	
Dieselfleet MSP 10W-30	
Change every 5000 miles/ 200 hours	
USE	CLIMATE
Biodiesel B5	Arctic
PRODUCT RECOMMENDATION 1	
Armado Synth MSP 5W-40	
Change every 5000 miles/ 200 hours	

DIFFERENTIAL REAR CONVENTIONAL Dana M60 Capacity: 2,9 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Change every 105000 miles	·	

TRANSMISSION AUTOMATIC 4R75E 4/1
Capacity: 13,1 liter (Dry fill)

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 15000 miles, change every 30000 miles

TRANSMISSION AUTOMATIC TorqShift 5/1 Capacity: 17,7 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 15000 miles, change every 3	000 miles	

## FORD (USA) E-150 E-150 6.0 TURBO DIESEL (2008-2010)



TRANSMISSION MANUAL 6/1 Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 100000 miles	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 6 months	'	

COOLING SYSTEM Capacity: 26 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 45000 miles/36 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 105000 miles/72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.