

FORD (USA) E-250 E-250 5.4 V8 (2012-2014)

ENGINE Triton
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20*Check every 1 months, change every 7500 miles/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20*Check every 1 months, change every 5000 miles/ 6 months/ 200 hours*

DIFFERENTIAL REAR LIMITED SLIP Dana M60
Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 105000 miles*

TRANSMISSION AUTOMATIC 4R75E 4/1
Capacity: 13,1 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032*Check every 15000 miles/ 12 months, change every 150000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032*Check every 15000 miles, change every 30000 miles*

FORD (USA) E-250 E-250 5.4 V8 (2012-2014)**TRANSMISSION AUTOMATIC** TorqShift 5/1

Capacity: 17,7 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Check every 15000 miles, change every 60000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

*Check every 15000 miles, change every 30000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 6 months

FORD (USA) E-250 E-250 5.4 V8 (2012-2014)**COOLING SYSTEM**

Capacity: 27,2 liter, Capacity: 29,1 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 45000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 6 months, change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.