

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**ENGINE**

Capacity: 5,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Check every 1 months, change every 7500 miles/ 6 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Check every 1 months, change every 5000 miles/ 6 months***DIFFERENTIAL REAR Ford 7.5 Conventional/Ford 8.8 Traction-Lok**

Capacity: 2,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140***Change every 105000 miles***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140***Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL Dana M60**

Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Change every 105000 miles***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Change every 50000 miles*

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**DIFFERENTIAL REAR CONVENTIONAL Dana M70FF**

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL Dana M70HD**

Capacity: 3,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL Dana M77FF**

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 50000 miles*

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**DIFFERENTIAL REAR CONVENTIONAL Dana M77HD**

Capacity: 3,9 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 105000 miles

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL Dana M80**

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 105000 miles

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

*Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL AND LIMITED SLIP Dana M60**

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 105000 miles

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 50000 miles

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**DIFFERENTIAL REAR LIMITED SLIP Dana M60**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 50000 miles***DIFFERENTIAL REAR LIMITED SLIP Dana M70FF**

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 50000 miles***DIFFERENTIAL REAR LIMITED SLIP Dana M70HD**

Capacity: 3,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 105000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 50000 miles*

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**TRANSMISSION AUTOMATIC 4R100 4/1**

Capacity: 16,1-16,7 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Check every 15000 miles, change every 30000 miles***TRANSMISSION AUTOMATIC 4R75E 4/1**

Capacity: 13,1 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Check every 15000 miles, change every 30000 miles***TRANSMISSION AUTOMATIC TorqShift 5/1**

Capacity: 16,6 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

*Check every 15000 miles, change every 30000 miles***TRANSMISSION MANUAL 6/1**

Capacity: 5,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Check every 6 months, change every 100000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

FORD (USA) E-450 E-450 6.8 V10 (2001-2008)**POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Check every 6 months***COOLING SYSTEM**

Capacity: 28,8 liter, Capacity: 30,8 liter (+ heater)

USE		CLIMATE
Normal, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 18	Coolant -26	

Check every 15000 miles, change every 30000 miles

USE		CLIMATE
Normal, yellow fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 45000 miles/ 36 months

USE		CLIMATE
First change only, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 18	Coolant -26	

Check every 15000 miles, change every 50000 miles

USE		CLIMATE
First change only, yellow fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.