PRODUCT RECOMMENDATION

FORD (USA) F-150, 12TH GEN. F-150 3.7 V6 TI-VCT 4X4 (2010-2011)

ENGINE Duratec 37
Capacity: 5,7 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Check every 1 months, change every 5000 miles/ 6 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Check every 1 months, change every 10000 miles/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 150000 miles

DIFFERENTIAL REAR
Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 150000 miles

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 150000 miles

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (USA) F-150, 12TH GEN. F-150 3.7 V6 TI-VCT 4X4 (2010-2011)

TRANSFERBOX
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	**ATF Dexron II-D**	

Change every 150000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	**ATF Dexron II-D**	

Change every 60000 miles

TRANSMISSION AUTOMATIC 6R80 6/1
Capacity: 11,7 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	**SP Matic 2032**	

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (USA) F-150, 12TH GEN. F-150 3.7 V6 TI-VCT 4X4 (2010-2011)

COOLING SYSTEM
Capacity: 15,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**
Check every 6 months, change every 50000 miles/ 36 months		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**
Check every 6 months, change every 100000 miles/ 72 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367