

FORD (USA) F-150, 12TH GEN. F-150 5.0 V8 TI-VCT (2010-2011)



ENGINE Coyote
Capacity: 7,3 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 5000 miles/ 6 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 10000 miles/ 12 months

DIFFERENTIAL REAR

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

TRANSMISSION AUTOMATIC 6R80 6/1

Capacity: 12,4 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032

Change every 150000 miles

FORD (USA) F-150, 12TH GEN. F-150 5.0 V8 TI-VCT (2010-2011)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

COOLING SYSTEM

Capacity: 16,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 50000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 100000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.