

# FORD (USA) F-250 (SUPER DUTY) F-250 5.4 V8 (1998-2004)

**ENGINE**

Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20***Check every 1 months, change every 5000 miles/ 6 months/ 200 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20***Check every 1 months, change every 3000 miles/ 3 months/ 200 hours***DIFFERENTIAL REAR** Dana S110/S130

Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 50000 miles***DIFFERENTIAL REAR CONVENTIONAL** Dana M80

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90***Change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90***Change every 50000 miles*

# FORD (USA) F-250 (SUPER DUTY) F-250 5.4 V8 (1998-2004)



## DIFFERENTIAL REAR LIMITED SLIP

Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 50000 miles*

## TRANSMISSION AUTOMATIC 4/1

Capacity: 16,6 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032***Check every 15000 miles, change every 30000 miles*

## TRANSMISSION MANUAL 6/1

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

PRODUCT RECOMMENDATION 3

**ATF Dexron II-D***Check every 6 months*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 12 months, change every 24 months*

# FORD (USA) F-250 (SUPER DUTY) F-250 5.4 V8 (1998-2004)



## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 6 months*

## COOLING SYSTEM

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 12</b>	<b>Coolant SP 11</b>	

*Check every 15000 miles, change every 50000 miles/ 36 months*

USE		CLIMATE
First change only, yellow fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 12</b>	<b>Coolant SP 11</b>	

*Check every 15000 miles, change every 100000 miles/ 72 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*