PRODUCT RECOMMENDATION

FORD (USA) F-250 (SUPER DUTY) F-250 6.2 V8 SUPER DUTY (2011-2013)

ENGINE 379 CID
Capacity: 6,6 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Change every 5000 miles/ 6 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Check every 1 months, change every 7500 miles/ 6 months

DIFFERENTIAL REAR CONVENTIONAL Ford 10.5
Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 150000 miles

DIFFERENTIAL REAR LIMITED SLIP Ford 10.5
Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 150000 miles

TRANSMISSION AUTOMATIC 5R110W 5/1
Capacity: 16,6 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	**SP Matic 2032**	

Change every 60000 miles

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (USA) F-250 (SUPER DUTY) F-250 6.2 V8 SUPER DUTY (2011-2013)

TRANSMISSION AUTOMATIC 6R140(W) 6/1
Capacity: 15,8-17,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	**SP Matic 2032**	

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM
Capacity: 20,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 6 months, change every 45000 miles/ 36 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 6 months, change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367