

# FORD (USA) F-450 (SUPER DUTY) F-450 6.8 V10 SUPER DUTY (2004-2008)



**ENGINE** Triton  
Capacity: 6,6 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Check every 1 months, change every 5000 miles/ 6 months*

USE  
Severe

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Check every 1 months, change every 3000 miles/ 3 months/ 200 hours*

**DIFFERENTIAL REAR CONVENTIONAL** Ford 10.5  
Capacity: 3,3 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

*Change every 150000 miles*

**DIFFERENTIAL REAR LIMITED SLIP** Ford 10.5  
Capacity: 3,3 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

*Change every 150000 miles*

**TRANSMISSION AUTOMATIC** TorqShift 5R110 5/1  
Capacity: 16,6 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Check every 15000 miles, change every 30000 miles*

# FORD (USA) F-450 (SUPER DUTY) F-450 6.8 V10 SUPER DUTY (2004-2008)



## TRANSMISSION MANUAL S6-650 6/1

Capacity: 5,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

Change every 60000 miles

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 6 months

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

Check every 6 months

## COOLING SYSTEM

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 12</b>	<b>Coolant SP 11</b>	

Check every 6 months, change every 50000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 12</b>	<b>Coolant SP 11</b>	

Check every 6 months, change every 100000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.