

# FREIGHTLINER SPRINTER GEN I SPRINTER

## 3500 CDI (2003-2006)



**ENGINE** OM612 DE27LA  
Capacity: 9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 22500 km/ 450 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40**

*Change every 22500 km/ 450 hours/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 11500 km/ 225 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40**

*Change every 11500 km/ 225 hours*

**DIFFERENTIAL REAR**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Gearlube GL-5 80W-90**

*Check every 45000 km/ 900 hours, change every 270000 km/ 5400 hours*

**TRANSMISSION AUTOMATIC 722.6xx 5/1**

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

# FREIGHTLINER SPRINTER GEN I SPRINTER

## 3500 CDI (2003-2006)



### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		
<i>Change every 24 months</i>		

### POWER STEERING MB LZS 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 4026</b>	<b>SP Matic 2032</b>	<b>ATF Dexron II-D</b>

### GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

### COOLING SYSTEM

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 11</b>	<b>Coolant SP 12 EVO</b>	

*Change every 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.