

GMC (USA / CAN) SONOMA GMT325

SONOMA 2.2 (2001-2003)

**ENGINE**

Capacity: 4,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Synfleet SHPD 10W-40***Change every 7500 miles/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Synfleet SHPD 10W-40***Change every 3000 miles/ 3 months***DIFFERENTIAL REAR**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 7500 miles***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 3000 miles, change every 15000 miles***TRANSMISSION AUTOMATIC 4L60-E 4/1**

Capacity: 4,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Change every 50000 miles***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Change every 15000 miles*

GMC (USA / CAN) SONOMA GMT325

SONOMA 2.2 (2001-2003)



TRANSMISSION MANUAL 5/1

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 24 months*

HYDRAULIC CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Almirol*Check every 7500 miles*

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50000 km/ 60 months*

GMC (USA / CAN) SONOMA GMT325

SONOMA 2.2 (2001-2003)

**COOLING SYSTEM**

Capacity: 9,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15****PRODUCT RECOMMENDATION 2****Coolant SP 15+***Change every 150000 miles/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.